



Model 5400 Band Saw



Consistent cutting power.

Capable of handling material up to 8" H x 12" W, the Pendu Model 5400 can be operated as a single unit or as part of a multi-head system. The top-powered feed system, in conjunction with the heavy-duty, hardened-steel 8' table top conveyor provides a positive feed both into and away from the blade. The system is hydraulically powered for a smooth, consistent feed at variable speeds. A 2"-wide Lennox band, tensioned by a pneumatic regulator, incorporates a unique outboard bearing design for the arbor shaft, resulting in a more stable platform for the drive wheels. Optional Equipment includes a ProScale Digital readout with motorized up and down height adjustment.

Specifications

Cutting Capacity	Up to 8" x 12"
Manual Height Adjustment	Standard
Variable Feed Speed	0 to 100 FPM
Infeed/Outfeed	Hydraulically Driven Top Hold Down Rolls
Table Top Conveyor	Hardened steel / 8' L
2" Lennox Band	Other Sizes Available
Drive Wheel / Idler Wheel	36" Diam. x 1 1/2" / 35" Diam. x 1 1/2"
Motor	40 HP TEFC Electric Motor
Band Tension	Pneumatic with Low Pressure Shut Off Switch



*Designers and Manufacturers
of Specialized Equipment*